

LMSD3050

Cup 2 SM Adjustable



Description



- The Cup 2 boasts a high lumen output to present your space in the best light
- Excellent glare control and available in all major lighting control types
- 45D tilt & 355 Degree rotation allow for increased aiming flexibility
- Get creative with any number of on-trend trim and reflector colour options
- Photometric data shown is for module and Individual lenses only
- Customisations available on request

Finish

Black/White/Gold 

Material

Aluminium



TECHNICAL CHARACTERISTICS

Light source: Bridgelux COB
 Output (W): 16W
 Voltage: 240V
 Color temperature: 2700K/3000K/4000K
 CRI: 90
 Installation Method: Ceiling Surface Mounted
 System Lumen: 1200lm
 System efficacy: 83lm/W
 Dimming Type: Non-Dim, Phase-Cut, DALI, Dim to Warm
 Life Time: 50.000h
 MacAdam steps: 3
 UGR: <19
 IP Rating: IP21

PHYSICAL CHARACTERISTICS

Dimensions: 390*64*85mmmm
 Cutout: N/A
 Rotate Angle: 355°
 Tilt Angle: 45°

Additional

Warranty: 3 Years
 (optional 5 year warranty on request)

LIGHT DISTRIBUTION for 3000K medium 32°

h(m)	E (lx)	Ø(m)
1	2895	Ø0.63
2	714.4	Ø1.28
3	311.0	Ø1.93
4	178.1	Ø2.57
5	109.0	Ø3.22



The photograph may not match the reference exactly. Please read the product description to identify the finish.