



LMDL3357

Edge Fixed

Description


- Compact mini design with black baffle for reduced glare
- CRI90 as standard, with all major control types supported
- Photometric data shown is for module and Individual lenses only
- Customisations available on request

Finish

Black/White

Material

Aluminium



35mm
5-25mm



TECHNICAL CHARACTERISTICS

Light source: Bridgelux COB
 Output (W): 6W
 Voltage: 240V
 Color temperature: 2700K/3000K/4000K
 CRI: 90
 Installation Method: Ceiling Recessed
 System Lumen: 360lm
 System efficacy: 60lm/W
 Dimming Type: Non-Dim, Phase-Cut, DALI, Dim to Warm
 Life Time: 50.000h
 MacAdam steps: 3
 UGR: <17
 IP Rating: IP21

PHYSICAL CHARACTERISTICS

Dimensions: Ø42*50mm
 Cutout: Ø35mm
 Rotate Angle: NA
 Tilt Angle: NA

Additional

Warranty: 3 Years
 (optional 5 year warranty on request)

LIGHT DISTRIBUTION for 2700K Narrow 15°

h(m)	E(lx)	Ø(m)
1.	110.5	Ø0.36
2.	28.52	Ø0.72
3.	14.32	Ø1.08
4.	6.85	Ø1.44
5.	4.60	Ø1.80

Photometric 2700K 15D Ra.90

The photograph may not match the reference exactly. Please read the product description to identify the finish.