




LMDL3358 Juno 40 Tilt

Description


- Compact mini design with black baffle for reduced glare
- Versatile 20° adjustable tilt
- CRI90 as standard
- IP54 rated, suitable for bathroom and outdoor application
- Customisations available on request

Finish
Black/White

Material
Aluminium



↻ 40mm
▨ 5-2.5mm



TECHNICAL CHARACTERISTICS

Light source: Bridgelux COB
 Output (W): 4W
 Voltage: 240V
 Color temperature: 2700K/3000K/4000K
 CRI: 90
 Installation Method: Ceiling Recessed
 System Lumen: 240lm
 System efficacy: 60lm/W
 Dimming Type: Non-Dim, Phase-Cut, DALI, Dim to Warm
 Life Time: 50.000h
 MacAdam steps: 3
 UGR: <17
 IP Rating: IP54

PHYSICAL CHARACTERISTICS

Dimensions: Ø46*57mm
 Cutout: Ø40mm
 Rotate Angle: NA
 Tilt Angle: 20°

Additional

Warranty: 3 Years
 (optional 5 year warranty on request)

LIGHT DISTRIBUTION for 2700K medium 15°

h(m)	E(lx)	Ø(m)
1100.1		Ø0.36
225.02		Ø0.72
311.12		Ø1.08
46.25		Ø1.44
54.00		Ø1.80

Photometric 2700K 15D Ra.90