

## LMLD0291

### Apex Track Light



#### Description


- Designed for commercial lighting applications - Retail and Hospitality
- Available in 25W, 30W and 35W
- Minimal design with integral driver
- DALI and Phase-Cut lighting control supported
- Customisations available on request

#### Finish

Black/White

#### Material

Aluminium



#### TECHNICAL CHARACTERISTICS

Light source: Bridgelux

Output (W): 25W/30W/35W

Voltage: 240V

Color temperature: 3000K/4000K/5000K

CRI: 90

Installation method: 3-Circuit Track Mounted

System Lumen: 2000lm/2400lm/2800lm

System efficacy: 80lm/watt

Dimming Type: Non-Dim, Phase-Cut, DALI, Dim to Warm

Life Time: 50.000h

MacAdam steps: 3

UGR: 19

IP Rating: IP20

#### PHYSICAL CHARACTERISTICS

Dimensions: Small: Ø65\*140mm/Medium: Ø70\*145mm,

Large: Ø75\*145mm

Cutout: NA




Rotate Angle: 355°

Tilt Angle: 90°


#### Additional

Warranty: 3 Years


(optional 5 year warranty on request)



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

