



LMSD3049

Ciro Mini SM

Description



- Fully adjustable, architectural surface mounted spot light
- Perfectly equipped for the commercial, or residential environment
- Supports all major lighting control types
- Strong lumen output with excellent anti-glare properties
- Customisations available on request

Finish

White

Material

Aluminium



TECHNICAL CHARACTERISTICS

Light source: Bridgelux COB
 Output (W): 8W
 Voltage: 240V
 Color temperature: 2700K/3000K/4000K
 CRI: 90
 Installation method: Ceiling Surface Mounted
 System Lumen: 680lm
 System efficacy: 85lm/watt
 Dimming Type: Non-Dim, Phase-Cut, DALI, Dim to Warm
 Life Time: 50.000h
 MacAdam steps: 3
 UGR: 19
 IP Rating: IP20

PHYSICAL CHARACTERISTICS

Dimensions: Ø47.5*139mm
 Cutout: N/A
 Rotate Angle: 355°
 Tilt Angle: 90°

Additional

Warranty: 3 Years
 (optional 5 year warranty on request)

LIGHT DISTRIBUTION for 3000K medium 23°

h(m)	E(lx)	Ø(m)
1	1660	Ø0.39
2	415.1	Ø0.79
3	184.5	Ø1.19
4	103.8	Ø1.59
5	66.41	Ø1.98

Photometric 3000K 36D Ra.90

The photograph may not match the reference exactly. Please read the product description to identify the finish.