

LM-MMR1205025/1506030

Tek Linear 4680 (Microprismatic + Module Reflector)

Description

- Modular design with push in/push out structure, and click to connect pre-wired trunking system
- Anti-glare with highly specular reflector optics
- Pendant, Surface mounted and recessed installation available
- HCL intelligent control with Casambi, Presence and Daylight harvesting Sensor, and Emergency kit optional
- Integrated Microprismatic and recessed Louvre diffuser
- Direct/indirect distribution available

Finish

Black/White/Silver

Material

Aluminium



80°

140°

TECHNICAL CHARACTERISTICS

Light source: Philips

Output (W): 1.2m 50W (25W ↑ +25W ↓)

1.5m 60W (30W ↑ +30W ↓)

Voltage: 240V

Color temperature: 3000K/4000K

CRI: 90

Installation method: Pendant, Recessed, Surface Mount

System Lumen: 1.2m 7000lm (3500lm ↑ +3500lm ↓)

1.5m 8400lm (4200lm ↑ +4200lm ↓)

System efficacy: 140lm/watt

Dimming Type: Non-Dim, Phase-cut dim

Life Time: 50.000h

MacAdam steps: 3

UGR: 14

IP Rating: IP20

PHYSICAL CHARACTERISTICS

Dimensions: 46.4*80*1126mm /46.4*80*1446mm

Cutout: NA


Rotate Angle: NA

Tilt Angle: NA

Additional

Warranty: 3 Years

(optional 5 year warranty on request)



Indirect/direct light

