

LMDL3835 Curve Fixed

Description


- Sleek deep recessed design with curved bezel
- UGR19 low glare and CRI90 as standard
- IP54 rated, suitable for bathroom and wet area application
- Customisations available on request

Finish

Black/White

Material

Aluminium



TECHNICAL CHARACTERISTICS

Light source: Bridgelux COB
 Output (W): 10W
 Voltage: 240V
 Color temperature: 2700K/3000K/4000K
 CRI: 90
 Installation Method: Ceiling Recessed
 System Lumen: 894lm
 System efficacy: 89.4lm/W
 Dimming Type: Non-Dim, Phase-Cut, DALI, Dim to Warm
 Life Time: 50.000h
 MacAdam steps: 3
 UGR: <19
 IP Rating: IP54

PHYSICAL CHARACTERISTICS

Dimensions: Ø75*50mm
 Cutout: Ø65mm
 Rotate Angle: NA
 Tilt Angle: NA

Additional

Warranty: 3 Years
 (optional 5 year warranty on request)

LIGHT DISTRIBUTION for 3000K Medium 38°

h(m)	E(lx)	Ø(m)
1	14071	Ø0.68
2	351.71	Ø1.36
3	156.31	Ø2.05
4	87.91	Ø2.73
5	56.26	Ø3.42



Ø75

50