

## LMDL3546 Snoot Trimless Adjustable

### Description


- Sleek deep recessed trimless design with adjustable snoot
- Versatile 20° adjustable tilt and 355° rotate angle
- UGR19 low glare and CRI90 as standard
- Customisations available on request

### Finish

Black/White

### Material

Aluminium



### TECHNICAL CHARACTERISTICS

Light source: Bridgelux COB  
 Output (W): 10W  
 Voltage: 240V  
 Color temperature: 2700K/3000K/4000K  
 CRI: 90  
 Installation Method: Ceiling Recessed  
 System Lumen: 800lm  
 System efficacy: 80lm/W  
 Dimming Type: Non-Dim, Phase-Cut, DALI, Dim to Warm  
 Life Time: 50.000h  
 MacAdam steps: 3  
 UGR: <19  
 IP Rating: IP20

### PHYSICAL CHARACTERISTICS

Dimensions: Ø78\*78mm  
 Cutout: Ø90mm  
 Rotate Angle: 355°  
 Tilt Angle: 20°

### Additional

Warranty: 3 Years  
 (optional 5 year warranty on request)

### LIGHT DISTRIBUTION for 2700K medium 15°

h(m)	E(lx)	Ø(m)
1100.1		Ø0.36
225.02		Ø0.72
311.12		Ø1.08
46.25		Ø1.44
54.00		Ø1.80

Photometric 2700K 15D Ra.90

90mm 10W IP21

