




LMDL3002 Acclaim Keyhole

Description


- Designed for accent lighting, hallways and highlighting of feature walls
- IP54 rated, suitable for application in bathrooms and general wet areas
- Deep set recessed with 25° tilt
- Customisations available on request

Finish
Black/White

Material
Aluminium



➤ Cutout: 82mm
⚙️ 5-25mm



TECHNICAL CHARACTERISTICS

Light source: Bridgelux COB
 Output (W): 10W
 Voltage: 240V
 Color temperature: 2700K/3000K/4000K
 CRI: 80/90/97
 Installation Method: Ceiling Recessed
 System Lumen: 700lm
 System efficacy: 70lm/W
 Dimming Type: Non-Dim, Phase-Cut, DALI, Dim to Warm
 Life Time: 50.000h
 MacAdam steps: 3
 UGR: <19
 IP Rating: IP54

PHYSICAL CHARACTERISTICS

Dimensions: Ø90*74mm
 Cutout: Ø82mm
 Rotate Angle: 355°
 Tilt Angle: 25°

Additional

Warranty: 3 Years
 (optional 5 year warranty on request)

LIGHT DISTRIBUTION for 3000K wide 36°

h(m)	E(lx)	Ø(m)
1	917.2	Ø0.58
2	229.3	Ø1.17
3	101.9	Ø1.76
4	57.30	Ø2.34
5	36.70	Ø2.98

Photometric 3000K 36D Ra.90



The photograph may not match the reference exactly. Please read the product description to identify the finish.