



## LMDL3142 Cup Adjustable

### Description

- Stylish and functional, the Cup is right at home in any Multi-residential, or Commercial setting
- Excellent glare control and available in all major lighting control types
- 45D tilt & 355 Degree rotation allow for increased aiming flexibility
- Get creative with any number of on-trend trim and reflector colour options
- Photometric data shown is for module and Individual lenses only
- Customisations available on request

### Finish



Black/White/Gold/Wood




### Material

Aluminium

62mm



62mm  
5-25mm



### TECHNICAL CHARACTERISTICS

Light source: Bridgelux COB  
 Output (W): 8W  
 Voltage: 240V  
 Color temperature: 2700K/3000K/4000K  
 CRI: 90  
 Installation Method: Ceiling Recessed  
 System Lumen: 550lm  
 System efficacy: 83lm/W  
 Dimming Type: Non-Dim, Phase-Cut, DALI, Dim to Warm  
 Life Time: 50.000h  
 MacAdam steps: 3  
 UGR: <19  
 IP Rating: IP21

### PHYSICAL CHARACTERISTICS

Dimensions: Ø60\*55mm  
 Cutout: 62°  
 Rotate Angle: 355°  
 Tilt Angle: 45°

### Luminaire

IP21 for indoor use  
 Warranty: 5 Years

### LIGHT DISTRIBUTION for 3000K medium 32°

h(m)	E(lx)	Ø(m)
1	1050	Ø0.62
2	262.6	Ø1.25
3	116.7	Ø1.88
4	65.65	Ø2.50
5	42.02	Ø3.13



The photograph may not match the reference exactly. Please read the product description to identify the finish.