

## LM-MD1205025/1506030

### Tek Linear 4680 (Microprismatic Diffuser)

#### Description

- Modular design with push in/push out structure, and click to connect pre-wired trunking system
- Anti-glare with highly specular reflector optics
- Pendant, Surface mounted and Recessed installation available
- HCL intelligent control with Casambi, Presence and Daylight harvesting Sensor and Emergency kit optional
- Microprismatic Opal Diffuser for glare reduction and even light distribution
- Direct/indirect distribution available

#### Finish

Black/White/Silver

#### Material

Aluminium



80°

140°

#### TECHNICAL CHARACTERISTICS

Light source: Philips

Output (W): 1.2m 50W (25W↑+25W↓)

1.5m 60W (30W↑+30W↓)

Voltage: 240V

Color temperature: 3000K/4000K

CRI: 90

Installation method: Pendant, Recessed, Surface Mount

System Lumen: 1.2m 7000lm (3500lm↑+3500lm↓)

1.5m 8400lm (4200lm↑+4200lm↓)

System efficacy: 140lm/watt

Dimming Type: Non-Dim, Phase-cut dim

Life Time: 50.000h

MacAdam steps: 3

UGR: 14

IP Rating: IP65

#### PHYSICAL CHARACTERISTICS

Dimensions: 46.4\*80\*1126mm /46.4\*80\*1446mm

Cutout: NA


Rotate Angle: NA

Tilt Angle: NA

#### Additional

Warranty: 3 Years

(optional 5 year warranty on request)



Indirect/direct light

