

## LM1205025/1506030

### Volt Linear 6585

#### Description

- Modular design with push in/push out structure, and click to connect pre-wired trunking system
- Anti-glare with highly specular reflector optics
- Pendant, Surface mounted and recessed installation available
- HCL intelligent control with Casambi, Presence and Daylight harvesting Sensor, and Emergency kit optional
- Integrated Microprismatic opal diffuser
- Direct/indirect distribution available

#### Finish

Black/White/Silver

#### Material

Aluminium



80°

140°

#### TECHNICAL CHARACTERISTICS

Light source: Philips

Output (W): 1.2m 12W ↑ 18W ↓ / 1.5m 15W ↑ 23W ↓

Voltage: 240V

Color temperature: 3000K/4000K/5000K

CRI: 90

Installation method: Pendant, Recessed, Surface Mount

System Lumen: 1.2m 2400lm ↓ 1600lm ↑

1.5m 3000lm ↓ 2000lm ↑

System efficacy: 130lm/watt

Dimming Type: Non-Dim, Phase-cut, DALI

Life Time: 50.000h

MacAdam steps: 3

UGR: 14

IP Rating: IP20

#### PHYSICAL CHARACTERISTICS

Dimensions: 65\*85\*1206mm / 65\*85\*1506mm

Cutout: NA


Rotate Angle: NA

Tilt Angle: NA


#### Additional

Warranty: 3 Years

(optional 5 year warranty on request)




Direct light



Indirect/direct light

A=1206mm,1506mm,3006mm



65mm

